



13 SEER AIR HANDLER



EFFICIENCY AND PERFORMANCE YOU CAN RELY ON

Engineered to match a variety of systems, Lennox air handlers are designed for quick, easy installation and service-friendly maintenance. Factory-installed thermostatic expansion valves also provide peak cooling performance.

The 13 SEER air handler features an anti-rust painted, galvanized steel cabinet, tested with 500 hours of salt spray to ensure durability. The fully insulated design helps minimize indoor noise level, and the three-fan-speed function provides ideal comfort.

Additional features include:

- Filter that can be cleaned and reinstalled for optimum air filtration
- Two drainage spouts for easy installation
- Multiple airflow design
 - Vertical up-flow
 - Vertical down-flow
 - Horizontal left-flow
 - Horizontal right-flow
- R-410 refrigerant, also compatible with R-22 systems
- Piston throttle device
- Complies with ARI 210/240 standard
- 1-year warranty

13 SEER AIR HANDLER PERFORMANCE SPECIFICATIONS

	Tonnage	Model	Power Supply [V-Ph-Hz]	Dimensions [inches]	Weight [lbs.]	Liquid Side/ Gas Side [in.]	Max. Refrigerant Pipe Length [ft.]	Max. Diff. Outdoor and Indoor Unit [ft.]	Drainage Pipe Outside Diameter [mm]	Shipping Per STD40HQ
AIR CONDITIONERS	1.5	LXGAHMD018130P4	208/230-1-60	18.125 x 41.375 x 20.5	114/128	3/8 / 3/4	150	33	Ø26.4	192
	2.0	LXGAHMD024130P4	208/230-1-60	18.125 x 41.375 x 20.5	114/128	3/8 / 3/4	150	33	Ø26.4	192
	2.5	LXGAHMD030130P4	208/230-1-60	18.125 x 41.375 x 20.5	119/132	3/8 / 3/4	150	33	Ø26.4	192
	3.0	LXGAHMD036130P4	208/230-1-60	19.625 x 46.5 x 21.625	136/152	3/8 / 3/4	150	50	Ø26.4	120
	3.5	LXGAHMD042130P4	208/230-1-60	19.625 x 46.5 x 21.625	141/156	3/8 / 3/4	150	50	Ø26.4	120
	4.0	LXGAHMD048130P4	208/230-1-60	22 x 54.5 x 24	172/187	3/8 / 7/8	150	50	Ø26.4	102
	5.0	LXGAHMD060130P4	208/230-1-60	22 x 54.5 x 24	172/187	3/8 / 7/8	150	50	Ø26.4	102
HEAT PUMPS	1.5	LXGAHMD018130P4	208/230-1-60	18.125 x 41.375 x 20.5	114/128	3/8 / 3/4	150	33	Ø26.4	192
	2.0	LXGAHMD024130P4	208/230-1-60	18.125 x 41.375 x 20.5	114/128	3/8 / 3/4	150	33	Ø26.4	192
	2.5	LXGAHMD030130P4	208/230-1-60	18.125 x 41.375 x 20.5	119/132	3/8 / 3/4	150	33	Ø26.4	192
	3.0	LXGAHMD036130P4	208/230-1-60	19.625 x 46.5 x 21.625	136/152	3/8 / 3/4	150	50	Ø26.4	120
	3.5	LXGAHMD042130P4	208/230-1-60	19.625 x 46.5 x 21.625	141/156	3/8 / 3/4	150	50	Ø26.4	120
	4.0	LXGAHMD048130P4	208/230-1-60	22 x 54.5 x 24	172/187	3/8 / 7/8	150	50	Ø26.4	102
	5.0	LXGAHMD060130P4	208/230-1-60	22 x 54.5 x 24	172/187	3/8 / 7/8	150	50	Ø26.4	102



© Lennox Industries Inc. 2010

Visit us at www.lennox.com, or contact us at 1-800-9-LENNOX.

PC62407